AIRTALK XS

Product information

Lightweight, monaural headset for air traffic control.
Used world wide

- Wideband audio components for HD audio and crystal clear communication
- Extendible headband for perfect fit to your head
- Acoustic Shock Protection for the safety of your hearing
- Quick Disconnect connector for adaption to all major telecommunication systems
- Ear cushions with cooling technology Coolmax® for best wearing comfort
- Diverse connection options and adjustments for nearly all Voice-communication-systems, including USB

TECHNICAL BASICS

SPEAKER	
Working principle	Dynamic
Impedance	600Ω ± 15% (1 kHz)
Sensivity	103dB ± 3dB (1mW)
Frequency response	100Hz to 10kHz

OTHER INFORMATION	
Weight	60g
Operation temperature	0˚C to +40˚C

MICROPHONE	
Working principle	Electret
Directivity	Bi-directional
Noise Cancelling	YES
Impedance	1,6kΩ (1 kHz)
Frequency response	60Hz to 12kHz
Sensivity	-51dB ± 3.5dB (1 kHz)
Sound pressure level	110dB S.P.L.
S/N ratio	58dB (1kHz)

More information about the Product and the corresponding accessories, connection cable and scope of delivery can be found at www.imtradex.com.

Imtradex Hör-/Sprechsysteme GmbH
Daimlerstraße 23 · D-63303 Dreieich · Tel.: +49 (0) 61 03 - 4 85 69 - 40 · Fax: +49 (0) 61 03 - 4 85 69 - 60 · E-Mail: info@imtradex.com · Web: www.imtradex.com